

# MICENAS AL3000



## Benefits

- Classic styled modern heritage luminaire
- No glazing panes offer high level of vandal resistance
- High performance optics with flat glass producing zero upward light

## Features

- Gravity cast aluminium body finished in a textured black polyester powder coating
- Hinge-up aluminium alloy upper cover with the same finish as the body, joined together through stainless steel hinges and safety clamps
- Stay-rod mechanism to support the canopy when open, for ease of maintenance
- Optical system incorporates a hydroformed and anodised reflector, and 4mm tempered clear flat glass
- Sealed optical system
- Galvanised steel control gear tray
- Integral gear

## Colours

- RAL9005 Black



	Lamp wattage and type	Lamp holder	Description	Weight (Kg)*	Windage (m²)
<b>AL3001</b>	70/100/150W SON-T	E27/E40	Flat glass; post mounted; integral gear	17.38	0.136
<b>AL3001</b>	70/100/150W HQI-E	E27	Flat glass; post mounted; integral gear	17.2	0.136
<b>AL3001</b>	125W HQL	E27	Flat glass; post mounted; integral gear	13.7	0.136

\*Max in range.



## Column and bracket options

Choose between fixed and base hinged

	6m	5m	4m		6m	5m	4m
<b>Fixed</b>				Base diameter (mm)	140/168	140/168	140/168
Tubular	TB060/SP1	TB050/SP1	TB040				
Tubular [Black]	TB060/SP1/2P9005	TB050/SP1/2P9005	TB040/2P9005	Shaft diameter (60mm spigot)	76	76	60/76
Classic	TB060/CL1	TB050/CL1	TB040/CL1				
Classic [Black]	TB060/CL1/2P9005	TB050/CL1/2P9005	TB040/CL1/2P9005	Base height (mm)	1250	1250	1250
<b>Base</b>							
Light duty	T061RLS/SP1	T051RLS/SP1	T041RLS/SP1	Flange plate (mm)	Type 1	Type 0	Type 0
Light duty [Black]	T061RLS/SP1/2P9005	T051RLS/SP1/2P9005	T041RLS/SP1/2P9005	Root length (mm)	1000	800	600
				Door opening (mm)	600 x 115	500 x 100	500 x 100
				Cable entry (root) (mm)	150 x 50	150 x 50	150 x 50

For flange plate add /FP: e.g. TB040/FP/CL2

### Accessories

**ELSA1/6A** Single phase, cut-out, 6A, termination plate




Columns and brackets finished hot dip galvanised to BSEN1461:1999

Where indicated, columns are spray painted with a long life 2-pack acrylic coat, wet finish 190 microns. RAL9005 Black.




## Key features




**Dimensions & Mounting**  
AL3000

Mounting height: 4m-6m



**Maintenance**


Access to lamp and gear via aluminium hinged upper cover, secured by stainless steel locking bolts



**AM3001**

100W HQI-E

Mounting height: 5m



**AM3001**

100W HQI-E

Mounting height: 5m

All dimensions are in mm.